

## The Breed *Deep* Timepiece

(BRD1901 – BRD1904)



### Setting Instructions

- 1) Unscrew the crown by rotating it counterclockwise until it is free from the case threads.
- 2) Pull the crown out two clicks.
- 3) Rotate the crown counterclockwise until the date indicator changes once.
- 4) Set the current time by rotating the crown counterclockwise;\*
  - for AM hours **do not** advance the hour hand past the 12 o'clock position,
  - for PM hours advance the hour hand past the 12 o'clock position **once**.
- 5) Push the crown in one click.
- 6) Set the current date by rotating the crown clockwise until the correct value is displayed.\*
- 7) Push the crown in one click to commence timekeeping.
- 8) Secure the crown by pressing in on it to overcome the spring resistance, then rotate clockwise to start the threads, then continue screwing the crown down until it is secured to the case. **Finger-tighten only.**

### Water Resistance Guidelines

**Note:** the screw down crown must be properly secured to the case to achieve the rated water resistance. Additionally, manipulation of the crown while the watch is in contact with water will negate the rated water resistance as water penetration may occur.

Rating	Submersible	Capacity of Resistance
No Marking	No	Splash/light contact only.
5ATM	No	Hand/dish washing.
10ATM	Yes	Low depth and short duration only.
20ATM	Yes	Short duration diving up to 5 meters.
25ATM+	Yes	Average depth and duration diving.

\* Setting the time to AM / PM accordingly ensures that the date indicator changes at midnight rather than noon. If the date indicator is changing in the afternoon advance the hour hand one full rotation (12 hours), then reset the date indicator as necessary.