

The Reign *Emery* Timepiece

(RN5001 – RN5006)

Mechanical automatic watches harness the kinetic energy contained within the natural movement of your arm to generate the force required to operate. The watch will commence operation after a sufficient volume of initial power has been generated by handling / wearing or by manually winding the crown. Supplemental winding through wear or manual winding will ensure sustained functionality and increase the duration in which the watch will continue to operate when unworn.



Setting Instructions

- 1) Pull the crown out two clicks.
- 2) Set the watch to AM hours by rotating the crown clockwise until the date indicator advances once.
- 3) Set the current time by rotating the crown clockwise.
 - for AM hours, do not advance the hour hand past the 12 o'clock position,
 - for PM hours, advance the hour hand past the 12 o'clock position *once*.
- 4) Push the crown in one click.
- 5) Set the current date by rotating the crown counterclockwise until the correct value is displayed.
- 6) Push the crown in one click.
- 7) Manually wind the movement by rotating the crown clockwise 15 – 30 times.

Note: Setting the time to AM / PM accordingly ensures the date indicator changes at midnight rather than noon. If the date indicator is changing in the afternoon, advance the hour hand one full rotation (12 hours), then reset the date indicator as necessary.

Water Resistance Guidelines

5 ATM - may be submerged for short durations, in normal temperature fresh water only. Not suitable for bathing, swimming, watersports, or diving. **Note:** Manipulation of the crown while the watch is in contact with water will negate the rated water resistance as water penetration may occur.